

# Visual Warning Systems

## ULTI VIRTUAL VISION

Flashing lights alert personnel of hidden movement, where there is obstructed visibility before the door starts moving, therefore improving productivity and dramatically enhancing the safety of your personnel and reducing damage to vehicles.

### Virtual Visibility

Sensors detect any movement on the opposite side of the doorway and lights flash red to indicate the need for caution when passing through the doorway. If there is no movement detected, the lights will remain solid green, as safe to pass through.

### Ideal for use in


- Any doorways or openings where visibility is reduced
- Hidden corners
- Doors without vision panels

[!\[\]\(faf942dc3e59ce8eb64b4ac481eca7e0\_img.jpg\) WATCH HERE](#)



### Characteristics

Standard Dimensions	1700mm
Minimum Length	300mm
Maximum Length	4000mm
Height Mounted from FFL	1000mm
IP Rating	IP67
Operating Temperature	-40°C to +45°C Storage



Detects Movement

## LED PRE-ANNOUNCE

LED lights alert personnel of door activation, enhancing the safety of your personnel and reducing damage to vehicles and the door itself.

### Safety First

LED Pre-Announce ensures personnel know when it is safe to pass through the door. Lights on both sides of the door, flash red as the door opens, and turn solid green once fully open. As the door is about to close, the lights briefly flash green then return to flashing red while closing, and remain solid red when closed.

### Ideal for use in


- Doors without vision panels
- Ulti Roll variants, Ulti Frigo 2, Ulti Spiral, Ulti Flex, Ulti Fold Value, Ulti Komby, Ulti EX5

[!\[\]\(bff896c19919791b89ab521f039b410a\_img.jpg\) WATCH HERE](#)



### Characteristics

Dimensions	1000mm
Height Mounted from FFL	1000mm
IP Rating	IP66
Operating Temperature	-20°C to +85°C Storage
Rated lifetime	50,000 hours



Detects Door Activation

# Visual Warning Systems

## SAFETY LED PUSH BUTTON

Alike the LED Pre-Announce system, this innovative push button alerts personnel of the door activation to further enhance safety. As it is the activation, it is super simple to use, whilst also being very visible.

### Safer Activation

The Safety LED Push Button ensures personnel know when it is safe to pass through the door by flashing red when pushed, as the door opens. Once fully open, the button turns green, and then briefly flashes green as a pre-closing alert, before returning to flashing red while closing. When not activated, the light on the button remains off.


### Ideal for use with

- Ulti Roll variants, Ulti Frigo 2, Ulti Spiral, Ulti Flex, Ulti Fold Value, Ulti Komby, Ulti EX5



### Characteristics

Dimensions	90mm diameter
IP Rating	IP65
Mounting in place of standard push button	



Detects Door Activation

 **WATCH HERE**